Weatherproof 12/24V Audio Unit RG-9451

clarion



Compact, Dustproof, Weatherproof and Vibration Resistant



Clarion's Rugged New Audio Unit Is Built to Withstand the Harsh Conditions Endured in Construction and Farming Machinery



Just because you have to work outdoors doesn't mean you should have to give up the comfort of a quality Audio Unit. That's why, at Clarion, our commitment to making superior in-vehicle products doesn't stop at regular cars. To meet the rigorous demands of work on a construction site or in an agricultural setting, we created the new RG-9451 Weatherproof Audio Unit. With a rugged, watertight design that keeps out dust and water and dampens vibrations, the RG-9451 lets you listen to your favourite broadcasts without worrying about the weather or the environment.

Main Features

- •Thanks to an extremely airtight design, the front panel of the RG-9451 stands up to dusty or rainy conditions (IP65 compliant).
- Vibration resistance guaranteed to 6.8 G.
- •12V or 24V connectability.
- AUX (external audio input) terminals are provided on both the front and rear panels, allowing playback of other audio sources such as digital terrestrial TV tuners and portable MP3 players.
- Selectable radio frequencies:

FM frequencies – 87.9 to 107.9 MHz (North America) 87.5 to 108.0 MHz (Europe, Other)

AM frequencies – 530 to 1710 kHz (North America) 531 to 1602 kHz (Europe) 531 to 1629 kHz (Other)

- •Up to 12 stations each for AM and FM bands can be stored in memory. Battery back-up retains memory of pre-set stations for 2 weeks.
- •The RG-9451 has a compact design, especially depthwise. So it fits snugly in a shallow 1-DIN slot.

Optional Accessory

SKA-852-100

•A dedicated speaker set for the RG-9451 is optionally available. Speaker diameter is 10 cm and impedance is 8 Ω .











3.5 mm AUX input

1-channel AUX (RCA input)





Clarion Canada Inc.

2239 Winston Park Dr. Oakville, ON L6H 5R1 TEL: (905) 829-4600 FAX: (905) 829-4608 Toll Free: 1-800-668-5612

