

Release the Power From Within



Great Looks and Sound with the Power to Back it up - High Output to Drive Your System



Sleek Black Anodized Aluminum Packed with Power - Ready to Add More Musical Presence to Any System



BC2
Optional Wired Remote Bass Control
● Remote Control for XH7110 Amplifier

Feature Comparison

	Maximum Power Output	4-Ohm	2-Ohm	Type	Number of Channels	Dimensions (W" x L" x H")	CEA 2006 Power Ratings
XH7110	850W	450W x 1	850W x 1	Class GH	Mono	16-1/32 x 9 x 2-5/8	460W x 1 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 68dB (Ref: 1W into 4Ω)
XH5410	680W	90W x 4	160W x 4	Class AB	4/3/2	14-11/16 x 9 x 2-5/8	100W x 4 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 86dB (Ref: 1W into 4Ω)
XH5210	340W	90W x 2	160W x 2	Class AB	2/1	12-7/16 x 9 x 2-5/8	95W x 2 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 86dB (Ref: 1W into 4Ω)
XR2120	570W	280W x 1	400W x 1	Class AB	Mono	14 x 8-1/2 x 2-3/16	280W x 1 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 70dB (Ref: 1W into 4Ω)
XR2420	480W	60W x 4	90W x 4	Class AB	4/3/2	14 x 8-1/2 x 2-3/16	60W x 4 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XR2220	280W	65W x 2	90W x 2	Class AB	2/1	11-1/8 x 8-1/2 x 2-3/16	65W x 2 RMS [4Ω @ 14.4V ≤1% THD+N] S/N 86dB (Ref: 1W into 4Ω)
XC6410	600W	85W x 4	125W x 4	Class D	4/3/2	8-3/4 x 6-7/8 x 2-3/16	150W x 4 RMS [2Ω @ ≤ 14.4V 1% THD+N] 85W x 4 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XC6210	350W	85W x 2	125W x 2	Class D	2/1	6-3/8 x 6-7/8 x 2-3/16	150W x 2 RMS [2Ω @ ≤ 14.4V 1% THD+N] 85W x 2 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)

More Gravity for the Bass Line



Seamless Parabolic Design Coupled with Dual Voice Coils to Maximize Bass Response



Formidable Bass Performance in a Unique Shallow-Mount Design for Flexible Installation



Developed Specifically to Deliver Big Bass Sound with a Relatively Small Investment



Feature Comparison

	Size	Maximum Power Handling	High Strength Stamped Steel	Dual Voice Coil	CEA-2031 Speaker Rating
WQ3010D	12"	1500W	●	●	Maximum RMS Power: 500watts Impedance: 4 ohms + 4 ohms
WQ2510D	10"	1500W	●	●	Maximum RMS Power: 500watts Impedance: 4 ohms + 4 ohms
WF2510	10"	900W	●	●	Maximum RMS Power: 300 watts Impedance: 4 ohms
WF2510D	10"	900W	●	●	Maximum RMS Power: 300 watts Impedance: 4 ohms + 4 ohms
WG3010	12"	900W	●	●	Maximum RMS Power: 300 watts Impedance: 4 ohms
WG2510	10"	900W	●	●	Maximum RMS Power: 300 watts Impedance: 4 ohms

Technology Resonating with Savvy



Multiaxial and Component Speakers Provide A Perfect Solution for Your Acoustic Environment



Feature Comparison

	Size	Maximum Music Power	Type	CEA-2031 Speaker Rating
SRQ1722S	6-3/4"	400W	2-Way Component System	RMS Power:55 watts Impedance: 4 ohms
SRQ1622S	6-1/2"	350W	2-Way Component System	RMS Power:55 watts Impedance: 4 ohms
SRQ6933R	6" x 9"	500W	Multiaxial 3-Way	RMS Power:80 watts Impedance: 4 ohms
SRQ1732R	6-3/4"	400W	Multiaxial 3-Way	RMS Power:55 watts Impedance: 4 ohms
SRQ1632R	6-1/2"	350W	Multiaxial 3-Way	RMS Power:55 watts Impedance: 4 ohms
SRQ6832C	6" x 8"	350W	Custom Fit Multiaxial 3-Way	RMS Power:55 watts Impedance: 4 ohms
SRQ1332R	5-1/4"	300W	Multiaxial 3-Way	RMS Power:35 watts Impedance: 4 ohms
SRQ212H	3/4"	250W	Tweeter	RMS Power:45 watts Impedance: 4 ohms



Full Range of Multiaxial and Coaxial Speakers to Easily Upgrade from Your Car's Factory System



Feature Comparison

	Size	Maximum Music Power	Type	CEA-2031 Speaker Rating
SRG6932R	6" x 9"	400W	Multiaxial 3-Way	RMS Power:50 watts Impedance: 4 ohms
SRG6832C	6" x 8"	300W	Custom Fit Multiaxial 3-Way	RMS Power:45 watts Impedance: 4 ohms
SRG1622R	6-1/2"	250W	Coaxial 2-Way	RMS Power:35 watts Impedance: 4 ohms
SRG1322R	5-1/4"	230W	Coaxial 2-Way	RMS Power:30 watts Impedance: 4 ohms
SRG1022R	4"	180W	Coaxial 2-Way	RMS Power:30 watts Impedance: 4 ohms
SRG5732C	5" x 7"	250W	Custom Fit Multiaxial 3-Way	RMS Power:40 watts Impedance: 4 ohms
SRG4622C	4" x 6"	200W	Custom Fit Coaxial 2-Way	RMS Power:30 watts Impedance: 4 ohms
SRG922C	3-1/2"	80W	Custom Fit Coaxial 2-Way	RMS Power:20 watts Impedance: 4 ohms